iDiPOS

BS200—C

Product Features

•Support U-disk

User can download attendance logs and upload self-defined background pictures through U-disk

•Scheduled bell

Scheduled bell can be integrated into fingerprint time and attendance device.It will not only save cost but also facilitate management.Users can set the duration and the period of scheduled bell.

Product Specification

Specification	BS200 - Fingerprint Time Attendance Terminal
Display	3" TFT
LED indicator/Buzzer	2 LED(Red/Green) / 1 Buzzer
Display Language	Standard: English
Greeting Voice	Upon Request: Multinational Language
Keypad & button	16 key numeric & Function keypad
Dimension	190 x 140 x 57 mm
Sensor	
Sensor Type / Resolution	Optical (500 dpi)
Sensing Area	18mm × 22 mm
Storage Capacity	
Fingerprint capacity	3,000
Transaction	120,000
RF reader	
ID Card: 125 KHZ	Optional
MIFARE: 13.56 MHz	Optional
HID	Optional
I-Class card	Optional
Communications	
RS-232/485	YES
TCP/IP	Yes
USB Client	N/A
USB Host	YES
GPRS	
Time Attendance	
Schedule Bell	Yes
Work Code	Yes
Operation Environment	
Power Consumption	DC 5V, 2A
Temperature	0℃ ~ 45℃
Humidity	20% ~ 80%
Verification	
1:1 (Time)	<0.5 sec
1:N (Time)	<2 sec
FAR	≤0.0001%
FRR	≤1%
Standards Compliance	CE, FCC
More Standard Function	
Short Message (SMS), Record checking, Ring bell, 9 digits-code, Time event transfer	
More Optional Function	
Web server, Printer, RIS, 14 digits-code, Backup battery, Soap function	

CE FC RoHS

IDIPOS
web site: www.idipos.com
Email: contact@idipos.com